200210054-1 10/626,361

IN THE CLAIMS:

A detailed listing of all claims is provided below.

1. (currently amended) In a pump having a rotary portion which compels the movement of a fluid by peristaltic compression of resilient tubing containing the fluid, a tube component comprising the following:

a plurality of adjacent resilient tubes; and

and the offset web are integrally formed, and each of the resilient tubes has a cross-sectional centerline occurring in a common plane and the offset web only interconnects the resilient tubes in an area outside of the common plane, and the rotary portion of the pump includes a rotary area of pump operation and the web is outside the rotary area of pump operation.

- 2-4. (cancelled)
- 5. (original) A tube component in accordance with claim 1, wherein the resilient tubes are fabricated from an elastomeric plastic material.
 - 6-12. (cancelled)

200210054-1 10/626,361

13. (currently amended) A method of assembling a pump having a rotary portion which compels the movement of a fluid by peristaltic compression of resilient tubing containing the fluid comprising the following:

providing a plurality of adjacent resilient tubes; and

offset web being integrally formed, and wherein each of the resilient tubes has a cross-sectional centerline occurring in a common plane, the rotary portion of the pump includes a rotary area of pump operation, and the resilient tubes are only interconnected with the offset web in an area outside of the common plane and in an area outside the rotary area of pump operation.

14-16. (cancelled)

17. (original) A tube component in accordance with claim 13, wherein providing a plurality of adjacent resilient tubes comprises providing resilient tubes fabricated from an elastomeric plastic material.

18. (cancelled)

--19. (New) A tube component in accordance with claim 1, wherein the rotary portion of the pump includes a rotary area of pump operation, and the web is outside the rotary area of pump operation.--